

# MOZZO 4S

## FEATURES & BENEFITS

- All Season tread design
- 3 Circumferential grooves for rapid water evacuation and extra grip on wet pavement
- Assymetric tread design for improved handling and cornering
- New silica tread compound improves grip and reduces rolling resistance



PRODUCT CODE	TIRE SIZE	LOAD RANGE	SIDE WALL	UTQG	TREAD DEPTH (32NDS)	SECTION WIDTH (INCH)	OVERALL DIAMETER (INCH)	MAX LOAD SINGLE/DUAL	MAXIMUM PRESSURE (PSI)	WEIGHT (LB)	TREAD CONSTRUCTION
1192	145/70R12 69T	SL	BW	400 A A	9.0	5.91	20.04	723	51	0	1P+2S
1150	165/70R13 79T	SL	BW	400 A A	9.3	6.69	22.13	963	51	13	1P+2S
1151	175/70R13 82T	SL	BW	400 A A	9.3	6.97	22.68	1047	51	14	1P+2S
1193	185/70R13 86T	SL	BW	400 A A	9.3	7.44	23.23	1168	51	15	1P+2S
1194	165/70R14 81T	SL	BW	400 A A	9.3	6.69	23.15	1019	51	13	1P+2S
1153	175/70R14 84T	SL	BW	400 A A	9.3	6.97	23.70	1102	51	15	1P+2S
1152	175/65R14 82H	SL	BW	400 A A	9.3	6.97	22.99	1047	51	14	1P+2S+1N
1196	185/65R14 86H	SL	BW	400 A A	9.3	7.44	23.46	1168	51	15	1P+2S+1N
1197	185/65R14 90S	XL	BW	400 A A	9.3	7.44	23.46	1323	50	15	1P+2S+1N
1198	165/60R14 75H	SL	BW	400 A A	9.3	6.69	21.81	853	51	13	1P+2S+1N
1154	185/60R14 82H	SL	BW	400 A A	9.3	7.44	22.76	1047	51	14	1P+2S+1N
1199	155/55R14 69H	SL	BW	400 A A	9.0	6.38	20.71	723	51	11	1P+2S+1N
1200	165/55R14 72H	SL	BW	400 A A	9.3	6.69	21.18	783	51	13	1P+2S+1N
1155	175/65R15 84H	SL	BW	400 A A	9.3	6.97	23.98	1102	51	16	1P+2S+1N
1201	185/65R15 88H	SL	BW	400 A A	9.3	7.44	24.45	1235	51	17	1P+2S+1N
1202	185/60R15 84H	SL	BW	400 A A	9.3	7.44	23.74	1102	51	16	1P+2S+1N
1191	165/55R15 75V	SL	BW	400 A A	9.1	6.69	22.17	853	51	13	1P+2S+1N
1187	165/55R15 75H	SL	BW	400 A A	9.1	6.69	22.17	853	51	13	1P+2S+1N
1173	185/55R15 82V	SL	BW	400 A A	9.3	7.64	23.03	1047	51	16	1P+2S+1N
1186	165/50R15 72V	SL	BW	400 A A	9.3	6.69	21.54	783	51	13	1P+2S+1N
1190	165/50R15 72H	SL	BW	400 A A	9.3	6.69	21.54	783	51	13	1P+2S+1N
1189	165/45R16 74V	XL	BW	400 A A	9.0	6.50	21.81	739	51	13	1P+2S+1N
1184	165/40R16 70V	XL	BW	400 A A	9.0	6.69	21.18	739	50	12	1P+2S+1N
1188	165/40R16 73V	XL	BW	400 A A	9.0	6.69	21.18	805	50	12	1P+2S+1N