

ST RADIAL

FEATURES & BENEFITS

- Circumferential grooves evacuate water in order to resist hydroplaning
- Spiral wrap technology improves uniformity and protects against the effects of heat buildup
- Dual angled sipes provide additional biting edges for extra grip on the road
- Continuous center ribs aid in keeping the trailer on track behind the tow vehicle



PRODUCT CODE	TIRE SIZE	LOAD RANGE	SIDE WALL	UTQG	TREAD DEPTH (32NDS)	SECTION WIDTH (INCH)	OVERALL DIAMETER (INCH)	MAX LOAD SINGLE/DUAL	MAXIMUM PRESSURE (PSI)	WEIGHT (LB)	TREAD CONSTRUCTION
5900	ST175/80R13 91/87L	C	BW	---	10.0	6.97	24.02	1360/1200	60	16	1P+2S
5901	ST185/80R13 94/89L	C	BW	---	10.0	7.24	24.65	1480/1280	60	17	1P+2S
5902	ST205/75R14 100/96L	C	BW	---	10.0	7.99	26.14	1760/1570	60	20	2P+2S
5903	ST205/75R15 101/97L	C	BW	---	10.0	7.99	27.13	1820/1610	60	22	2P+2S+1N
5904	ST205/75R15 107/102L	D	BW	---	10.0	7.99	27.13	2150/1870	75	23	2P+2S+1N
5905	ST215/75R14 102/98L	C	BW	---	10.0	8.50	26.69	1870/1650	60	22	2P+2S
5906	ST225/75R15 107/102L	C	BW	---	10.0	8.78	28.31	2150/1870	60	25	2P+2S+1N
5907	ST225/75R15 113/108L	D	BW	---	10.0	8.78	28.31	2540/2200	75	27	2P+2S+1N
5908	ST225/75R15 117/112L	E	BW	---	10.0	8.78	28.31	2830/2470	90	27	2P+2S+1N
5909	ST235/80R16 123/119L	E	BW	---	10.0	9.25	30.79	3420/3000	90	33	2P+2S+1N
5910	ST235/85R16 125/121L	E	BW	---	10.0	9.25	31.73	3640/3200	90	34	2P+2S+1N
5911	ST235/85R16 128/124L	F	BW	---	10.0	9.25	31.73	3960/3520	105	38	3P+2S+2N